

MATERIAL SAFETY DATA SHEET

HMIS CODES:

H	F	R	P
0	2	0	A

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administrator
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

IDENTITY (AS USED ON LABEL AND LIST):

JOMAR THE HEAVYWEIGHT

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name:
JOMAR INTERNATIONAL DRIVE

Emergency Telephone Number:
(586) 268-1220

Address (Number, Street, City, State, and ZIP Code):
7243 MILLER DRIVE

Telephone Number for Information:
(586) 268-1220

SUITE 100

Date Prepared: August 27, 2010

WARREN, MI 48092

Signature of Preparer (optional):

Section II - Hazardous Ingredients/Identity Information

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY: COMMON NAME(S))	OSHA PEL	ACGIH TLV	OTHER LIMITS Recommended	% (optional)
ISOPROPANOL [CAS#67-63-0]	400 ppm	400 ppm	N/A	8 - 13%
BUTYL CELLOSOLVE [CAS#111-76-2]	50 ppm	25 ppm	N/A	20 - 25%

Section III - Physical/Chemical Characteristics

Boiling Point:	180°F	Specific Gravity (H2O =1):	1.41
Vapor Pressure (mm Hg):	.88	Melting Point:	N/A
Vapor Density (AIR = 1):	> 1	Evaporation Rate (Butyl Acetate = 1):	0.6

Solubility in Water: SLIGHT

Appearance and Odor: WHITE PASTE - MILD ODOR

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 82°F (28°C) ASTM METHOD D93-80	Flammable Limits: 921°F (494°C) IGNITION TEMPERATURE	LEL: 1.1%	UEL: 10.6%
--	--	--------------	---------------

Extinguishing Media: CARBON DIOXIDE OR DRY CHEMICAL OR WATER.

Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards:
CONTACT WITH STRONG OXIDIZERS MAY CAUSE FIRES OR EXPLOSIONS. CARBON MONOXIDE MAY BE RELEASED.

Section V - Reactivity Data		JOMAR THE HEAVYWEIGHT	
Stability:	Unstable:		Conditions to Avoid: N/A
	Stable:	X	

Incompatibility (Materials to Avoid):
LIQUID OXYGEN SYSTEMS, LIQUID SODIUM, GASEOUS FLUORINE, STRONG OXIDIZERS.

Hazardous Decomposition or Byproducts: N/A

Hazardous Polymerization:	May Occur:		Conditions to Avoid: N/A
	Will Not Occur:	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? YES	Skin? YES	Ingestion? YES
--------------------	-----------------	-----------	----------------

Health Hazards (Acute and Chronic): NONE

Carcinogenicity:	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
------------------	---------	---------------------	--------------------

Signs and Symptoms of Exposure:
INHALATION: POSSIBLE DIZZINESS IF USED IN CONFINED AREA.
SKIN: MAY CAUSE MILD IRRITATION TO SENSITIVE SKIN.

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN.

Emergency and First Aid Procedures:
EYE CONTACT: FLUSH EYES WITH WATER.
SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE.
INHALATION: MOVE TO WELL VENTILATED AREA. INGESTION: CONSULT A PHYSICIAN.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled:
NORMAL GOOD HOUSEKEEPING PROCEDURES.

Waste Disposal Method:
DISPOSAL TO BE DONE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Precautions to Be Taken in Handling and Storing:
STORE AWAY FROM HEAT OR OPEN FLAME. CLOSE CONTAINER AFTER USE.

Other Precautions:
WEAR PROTECTIVE GLOVES TO PREVENT POSSIBLE SKIN ABSORPTION AND DERMATITIS. KEEP OUT OF REACH OF CHILDREN.

Section VIII - Control Measures

Respiratory Protection (Specify Type):
AVOID BREATHING OF FUMES. IF USED IN A CONFINED AREA, A RESPIRATOR MAY BE NECESSARY.

Ventilation:	Local Exhaust: NORMAL VENTILATION IS ADEQUATE.	Special: N/A
	Mechanical (General): N/A	Other: N/A

Protective Gloves: MAY BE NECESSARY FOR SENSITIVE SKIN.	Eye Protection: KEEP OUT OF EYES. WEAR PROTECTIVE GOGGLES WHERE NECESSARY.
--	---

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: WASH UP WITH SOAP AND WATER AFTER USE.