Lockwing



Utility Gas Ball Valve, Angle Body, Full Port, Meter Nut, Swivel Connection, Service Bypass, 125 PSIG



125-LWBP-SA

Features

- 20LT or 30LT
- Tamper Resistant Lockwing Cap
- 2 FKM O-Rings
- Meter Nut and Swivel Connects Directly to Meter
- Full Port Design to Accommodate
- Industry Leading Stop Changers
- Lockwing Accommodates Standard Barrel Locks
- Maintenance Free Design
- Patented Security Shutter and Lockwing Tab
 US Patent No. 6,648,009
- 100% Leak Tested
- 100% Made in Italy
- · Leakproof Stem Lifetime Warranty

Approvals .


- CSA Certified
 - o CGA 3.16 (125G)
 - · ANSI B16.33 (125G)
- Meets or exceeds applicable part of DOT 192
- MSS SP-110


Pressure Rating

- 125 PSIG
- Temp range: -40°F to 300°F



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.





Material Specifications

No.	Part	Materials					
1	Body	Brass - C37700					
2	End Connection	Brass - C37700					
3	Ball	Chrome Plated Brass - C37700					
4	Seat (2)	PTFE G300					
5	Stem	Brass - C38500					
6	Packing	Buna-N					
7	Stem O-ring (2)	FKM					
8	Packing Gland	Brass - C38500					
9	Lockwing Cap	Brass - C37700					
10	Screw	304 Stainless Steel					
11	Union Nut	Brass - C37700					
12	Tail Piece	Brass - C38500					
13	Bypass Plug	Brass - C38500					
14	Bypass Set Screw*	Brass - C38500					
15	Bypass O-ring*	Viton [®]					
16	Bypass Cap	Brass - C38500					
*Not 9	*Not Shown						

Dimensions

Part No.	Size	Α	В	C	D	E	F
245-005BA	1"	3.52	2.09	2.09	0.94	0.59	20LT
245-105BA	1"	3.52	2.09	2.09	0.94	0.59	30LT