



Carbon Steel Ball Valve

3 Piece 4 Bolt, Swing Out Body, Full Port, Socket Weld Connection, Stainless Steel Trim, 1000 WOG

S-CS-1000N-SS-4B



FEATURES

Latch Lock Handle May be Locked in Open or Closed Position 100% Leak Tested 29 in-Hg Vacuum Rating Wetted Surfaces Contain Less than .25% Lead Content Mating Flanges Available Repair Kits Available

CERTIFICATIONS/APPROVALS


UL Listed (1/4" - 2")


- MHKZ Manual Valves
- YSDT LP Gas Shut-Off Valves
- YQAR Anhydrous Ammonia Shut-Off Valves
- YRBX Flammable Liquid Shut-Off Valves

NACE Certified MSS SP-110 ANSI B16.11 Conforms to API 598

Buy American Act Compliant

VALVE SEAT RATING 1000 WOG - 150 WSP





MATERIALS

No.	Part	Material
1	Body	WCB Carbon Steel
2	End Cap (2)	WCB Carbon Steel
3	Ball	CF8M Stainless Steel
4	Seat (2)*	Hostaflon® TFM 1600
5	Stem	316 Stainless Steel
6	Packing (2)*	RPTFE
7	Stem Seal*	Hostaflon® TFM 1600
8	Packing Gland	1045 Carbon Steel
9	Body Seal (2)*	Hostaflon® TFM 1600
10	Handle	A283 Carbon Steel
11	Handle Nut	A283 Carbon Steel
12	Lock Washer	A283 Carbon Steel
13	Body Bolt (4)	A283 Carbon Steel
14	Body Lock Washer (4)	A283 Carbon Steel
15	Body Nut (4)	A283 Carbon Steel

^{*}Included in repair kit

DIMENSIONS

Part No	Size	Α	В	С	D	Torque
500-503	1/2"	2.76	2.38	4.30	0.56	80
500-504	3/4"	3.03	2.87	5.81	0.81	150
500-505	1"	3.63	2.95	5.81	1.00	250
500-506	1-1/4"	4.14	3.66	7.44	1.25	320
500-507	1-1/2"	4.73	3.94	7.44	1.50	400
500-508	2"	5.43	4.25	7.81	1.97	480