

Stainless Steel Ball Valve 3 Piece 4 Bolt • Swing Out Body • Full Port • Threaded x Flanged Connection with Drain • Reversed Handle • 1000 WOG




T-SS-1000N-4B

Features


- Type B flange face
- Latch lock may be locked in open or closed positions
- 29 in-Hg vacuum rating
- 100% leak tested
- Wetted surfaces contain less than .25% lead content
- Repair kits available

Valve Seat Rating 1000 WOG - 150 WSP





 $\textbf{WARNING:} \ This \ product \ can \ expose \ you \ to \ chemicals \ including \ diisononyl \ phthalate$ (DINP), which is known to the State of California to cause cancer, and diisononyl phthalate (DINP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Material Specifications

| No. | Part | Materials | | | | | | |
|-----|---------------|-------------------|--|--|--|--|--|--|
| 1 | Body | A351-CF8M | | | | | | |
| 2 | Body Cap | A351-CF8M | | | | | | |
| 3 | Square Flange | A351-CF8M | | | | | | |
| 4 | Ball | A351-CF8M | | | | | | |
| 5 | Stem | SS 316 | | | | | | |
| 6 | Seat | TFE/RTFE/TFM 1600 | | | | | | |
| 7 | Stem Seal | TFE/RTFE/TFM 1600 | | | | | | |
| 8 | Stem Packing | TFE/RTFE/Graphite | | | | | | |
| 9 | Union Seal | TFE/RTFE/TFM 1600 | | | | | | |
| 10 | Spring Washer | SS 304 | | | | | | |
| 11 | Washer | SS 304 | | | | | | |
| 12 | Gland | SS 316 | | | | | | |
| 13 | Handle Nut | SS 304 | | | | | | |
| 14 | Cap Nut | SSS 304 | | | | | | |
| 15 | Handle | SS 304 | | | | | | |
| 16 | Cap Bolt | SS 304 | | | | | | |
| | | | | | | | | |

^{*}Included in repair kit

Dimensions

| Part No. | Size | Α | В | C | D | Torque |
|----------|------|------|------|------|------|--------|
| 501-358 | 2" | 7.67 | 2.90 | 7.99 | 1.97 | 480 |