THREAD SEALANT















| OTHER BRANDS | WHITE STUFF | GREEN STUFF | HEAVYWEIGHT | WOG PLUS | COPPER ANTI-SEIZE | NICKEL ANTI-SEIZE |
|--------------------|---|--------------------------------|---|---------------------|---|-----------------------------------|
| JC WHITLAM | SELECT-UNYTE | T-U TYPE 555 | SELECT-UNYTE | STEEL-UNYTE | TALON COPPER | TALON NICKEL |
| BLUE MONSTER | BLUE MONSTER PTRE PIPE THREAD SEALANT | BLUE MONSTER THREAD SEALANT | BLUE MONSTER PTRE PIPE THREAD SEALANT | - | BLUE MONSTER COPPER ANTI-SEIZE LUBRICANT | BLUE MONSTER NICKEL ANTI-SEIZE |
| RECTORSEAL | T+2 | #5, #5 SPECIAL, #5 SUB-ZERO | T+2 | TRU-BLU | COPPER-RICH | NICKEL-RICH |
| FEDERAL PROCESS | GASOILA SOFT-SET THREAD SEALANT PTFE | GASOILA-NT | GASOILA SOFT-SET THREAD SEALANT PTFE | GASOLIA HARD SET | - | GASOLIA THRED GARD |
| HARVEY | TFE PASTE | YELLOW SEALANT | TFE PASTE | - | - | - |
| HERCULES | REAL-TUFF | - | REAL-TUFF | HERCULES GRRIP | - | - |
| OATEY | GREAT WHITE | OATEY GREAT BLUE | GREAT WHITE | - | - | - |
| IPS | WHITE SEAL | GREEN STUFF | WHITE SEAL | - | - | - |

USAGE CHART

| ACETYLENE | - | - | - | - | - | | FREON (ALL) | | | | | | | NATURAL GAS | | | | | | |
|----------------------------|---|---|---|---|---|---|------------------------------|---|---|---|---|---|---|------------------------|---|---|---|---|---|---|
| ACIDS, DILUTED | • | • | | • | • | - | GASOLINE ² | • | • | • | • | - | - | NITROGEN, GASEOUS | • | • | • | • | • | • |
| AIR, COMPRESSED GASEOUS | • | • | | • | • | | GASOHOL | | - | - | - | - | - | OXYGEN | - | - | - | - | - | - |
| ALKALIS DILUTED | • | • | | | | | GLYCOL | • | • | • | - | - | - | PETROLEUM SOLVENTS | • | • | | • | - | - |
| AMMONIA | | | | | | | HEATING OILS | | | | | - | - | PROPANE | | | | | - | - |
| ALIPHATIC SOLVENTS | • | • | | • | - | - | HELIUM GASEOUS | • | • | • | • | - | - | REFRIGERATION GASES | • | • | • | • | • | • |
| BRINE | | | | | | | HYDRAULIC OILS | | | | | - | - | SOAP, LIQUID | | | | | | |
| BUTANE | | | | | - | - | HYDROGEN | • | | | - | - | - | STEAM LINES | | • | | | | |
| CARBON DIOXIDE | • | • | | • | • | ۵ | INERT GASES GASEOUS | • | • | • | • | • | | SUGAR, LIQUID | • | • | • | • | • | ۵ |
| CASTOR OILS | | | | | - | - | JET FUEL (JP 3,4,5 | | | | | - | - | VEGETABLE OILS | | | | | - | - |
| CHLORINATED WATER | • | • | | • | • | - | KEROSENE | • | • | • | • | - | - | WATER (HOT OR COLD) | • | • | • | • | • | ۵ |
| CORROSIVES | | - | | - | | - | LACQUER | • | | | | - | - | XYLOL | | - | | | - | - |
| COAL TAR NAPHTHA | • | • | | - | - | - | LIQUEFIED PETROLEUM GASES | • | • | • | • | - | - | | | | | | | |
| CUTTING OILS | • | • | | • | - | - | MANUFACTURED GASES | _ | • | • | • | - | - | | | | | | | |
| DIESEL FUEL OIL | | • | | | - | - | MINERAL OILS | | • | | | - | - | | | | | | | |
| FATTY ACIDS (LIQUIDS) | • | - | | - | • | - | NAPHTHA | | - | • | • | - | - | | | | | | | |

*CONTACT JOMAR FOR COMPATIBLE GASOLINE BLENDS

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.

THREAD SEALANT





White Stuff

Slow-Drying, Soft-Set, PTFE Thread Sealant

| PART NUMBER | SIZE | | |
|-------------|------------|----|----|
| 400-001 | 2 OZ. TUBE | 72 | 11 |
| 400-002 | 4 OZ. CAN | 24 | 13 |
| 400-003 | 8 OZ. CAN | 24 | 20 |
| 400-004 | 16 OZ. CAN | 12 | 22 |
| 400-005 | 32 OZ. CAN | 12 | 39 |

Jomar's White Stuff is a slow drying, soft setting, non-hardening PTFE pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, anti-galling, noncorrosive, nontoxic and will not harden in can.









Green Stuff

Slow-Drying, Soft-Set, General Purpose Thread Sealant

| PART NUMBER | SIZE | | |
|-------------|------------|----|----|
| 400-101 | 2 OZ. TUBE | 72 | 11 |
| 400-102 | 4 OZ. CAN | 24 | 13 |
| 400-103 | 8 OZ. CAN | 24 | 20 |
| 400-104 | 16 OZ. CAN | 12 | 22 |
| 400-105 | 32 OZ. CAN | 12 | 39 |

Jomar's Green Stuff is a slow drying, soft setting, non-hardening pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, antigalling, noncorrosive, nontoxic and will not harden in can.











Heavyweight

Slow-Drying, Soft-Set, Extra PTFE Thread Sealant

| PART NUMBER | SIZE | | |
|-------------|------------|----|----|
| 400-202 | 4 OZ. CAN | 24 | 11 |
| 400-203 | 8 OZ. CAN | 24 | 13 |
| 400-204 | 16 OZ. CAN | 12 | 22 |

Jomar's Heavyweight is a slow drying, soft setting, non-hardening industrial PTFE pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, anti-galling, noncorrosive, nontoxic and will not harden in can.







THREAD SEALANT





WOG Plus

Fast-Drying, Hard-Set, Thread and Gasket Sealant

| PART NUMBER | SIZE | CASE | WEIGHT |
|-------------|-----------|------|--------|
| 400-302 | 4 OZ. CAN | 24 | 12 |
| 400-303 | 4 OZ. CAN | 24 | 21 |
| 400-304 | 8 OZ. CAN | 12 | 19 |

Jomar's WOG Plus is a fast drying, hard setting, semi-paste, thread and gasket sealer. It remains flexible, so vibrations will not loosen connection. WOG Plus seals tightly but allows for disassembly without damage to parts. It is lead free, halogen free, noncorrosive and nontoxic.







Copper Anti-Seize

High Temperature Anti-Seize Lubricant and Thread Sealant

| PART NUMBER | SIZE | | |
|-------------|------------|----|----|
| 400-403 | 8 OZ. TUBE | 24 | 19 |
| 400-404 | 16 OZ. CAN | 12 | 15 |

Jomar's Copper Anti-Seize is a copper based anti-seize lubricant and thread sealant for high temperatures. It produces a permanent leakproof metallic seal under pressure, yet prevents seizing, galling, freezing, and tearing, even under extreme conditions. It is lead free, noncorrosive, nontoxic, and will not harden in can.







Nickel Anti-Seize

High Temperature Nickel Anti-Seize Lubricant and Thread Sealant

| PART NUMBER | SIZE | CASE | WEIGHT |
|-------------|------------|------|--------|
| 400-503 | 8 OZ. CAN | 12 | 19 |
| 400-504 | 16 OZ. CAN | 12 | 15 |

Jomar's Nickel Anti-Seize is a non-seizing, nickel based, lubricant and thread sealant. It may be used to prevent seizing, corrosion and galling where extreme temperature conditions exist. It contains a high percentage of microfine nickel flakes and is fortified with high quality rust and corrosion inhibitors. It is lead free, nontoxic, and will not harden in can.



