Dielectric UnionGalvanized FIP x FIP • 250 PSI





Galvanized FIP x FIP

Features

- Prevents Accelerated Corrosion
- Buna Seats: -20°F to 180°F

Approvals


- ANSI B1.20.1
- ASSE 1079

Pressure Rating

250 PSI



 $\textbf{WARNING:} \ This \ product \ can \ expose \ you \ to \ chemicals \ including \ lead, \ which \ is \ known$ to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Material Specifications

No.	Part	Materials
1	Body	Steel - Zinc Plated
2	Tail Piece	Steel - Zinc Plated
3	Union Nut	Steel - Zinc Plated
4	Dielectric Ring	Nylon 66
5	Gasket*	Buna-N

Dimensions

Part No.	Size	Α	В
701-413	1/2" FIP x 1/2" FIP	2.14	1.61
701-414	3/4" FIP x 3/4" FIP	2.21	1.83
701-415	1" FIP x 1" FIP	2.54	2.58
701-416	1-1/4" FIP x 1-1/4" FIP	2.73	2.96
701-417	1-1/2" FIP x 1-1/2" FIP	2.73	3.75
701-418	2" FIP x 2" FIP	3.12	4.30