

Thread Sealant



Slow-Drying, Soft-Set, General Purpose Thread Sealant



Green Stuff

Description

Jomar's Green Stuff is a slow drying, soft setting, non-hardening pipe thread compound. It will not transfer taste or odor to the system being sealed. Excellent for food and water systems. It is lead free, anti-galling, non-corrosive, nontoxic, and will not harden in can.

Temperature and Pressure Ratings

Brushable to: -50°F (-45°C)
 Temperature Range: -50°F to 400°F (-45°C to 204°C)
 Pressure Ratings: Gas – 3000 PSI (211 kg/cm²)
 Liquid – 6000 PSI (422 kg/cm²)

VOC: 342 g/l

Approvals

- NSF Certified
 - NSF 14 (PW, DWV, SW)
 - NSF 61 (C.HOT 180°F)
 - NSF 372
- CSA Certified (1/4" – 2")
 - CAN/ULC-S642 (125 PSIG)
 - ANSI LC7 (125 PSIG)
- Meets Mil. Spec. TT-S-1732

Directions

Stir well before using. Clean threads. Brush liberally onto male threads only. Apply appropriate torque to joint as required.

Part #	Size	Case Qty
400-101	2 oz tube	72
400-102	4 oz can	24
400-103	8 oz can	24
400-104	16 oz can	12
400-105	32 oz can	12

Recommended for use with:


- | | | |
|--|---|---|
| <ul style="list-style-type: none"> • Acids, Diluted • Air, Compressed Gaseous • Alkalis, Diluted • Ammonia • Aliphatic Solvents • Brine • Butane • Carbon Dioxide • Castor Oils • Chlorinated Water • Coal Tar Naphtha • Cutting Oils • Diesel Fuel Oil | <ul style="list-style-type: none"> • Freon (All) • Gasoline* • Glycol • Heating Oils • Helium Gaseous • Hydraulic Oils • Hydrogen • Inert Gases, Gaseous • Jet Fuel (JP 3,4,5) • Kerosene • Lacquer • Liquefied Petroleum Gases • Manufactured Gases | <ul style="list-style-type: none"> • Mineral Oils • Natural Gas • Nitrogen, Gaseous • Petroleum Solvents • Propane • Refrigeration Gases • Soap, Liquid • Steam Lines • Sugar, Liquid • Vegetable Oils • Water (Hot or Cold) |
|--|---|---|

NOT FOR USE ON OXYGEN SYSTEMS

*Contact Jomar for compatible blends

Recommended for use on:

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> • All types of metal • ABS • PVC • CPVC | <ul style="list-style-type: none"> • Delrin • Zytel • Fiberglass • Nylon | <ul style="list-style-type: none"> • Polypropylene • Polybutylene • Polyethylene |
|--|--|---|

 **Precautionary Statements**
 P264: Wash skin thoroughly after handling. P280: Wear protective gloves and eye protection. P303 + P361: IF ON SKIN, immediately remove all contaminated clothing and wash before reuse. P305 + P351: IF IN EYES, remove contact lenses if present and easy to do so, rinse with water for several minutes. P337 + P313: If eye or skin irritation persists – get medical advice/attention. P403 + P223: Store in a cool, well-ventilated place. Keep container tightly closed.