


## Lead Free Brass Ball Valve

2 Piece, Full Port, Solder Connection, Long Bonnet Neck, T-Handle, 600 WOG

**JF-100SLBG**



### FEATURES

- Dezincification Resistant Brass Alloy
- Long Bonnet Neck for Easier Access in Hard to Reach Applications
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested

### CERTIFICATIONS/APPROVALS

- IAPMO Certified
  - NSF/ANSI/CAN 61
  - NSF/ANSI/CAN 372
  - NSF/CAN 14
- Solder-Joint conforms to ASME B16.22
- MSS SP-110

### PRESSURE/TEMPERATURE RATING

- 600 WOG
- Temperature Range: -20° F to 300° F

### MATERIALS

No.	Part	Material
1	Body	Lead Free Brass - C46500
2	Seat	PTFE
3	Ball	304 Stainless Steel
4	O-Ring	NBR
5	Extension Sleeve	Brass
6	Packing	PTFE
7	Packing Nut	Brass
8	Handle Nut	Plated Steel
9	Stem	Brass
10	O-Ring	Viton
11	Cap	Lead Free Brass - C46500
12	Handle	Plated Steel

### DIMENSIONS

Part No	Size	W	H	L
100-153G	1/2"	1.99	3.47	3.94
100-154G	3/4"	2.71	3.59	3.94