



Brass Ball Valve

2 Piece, Full Port, Press Connection, 250 WOG

JP-100



FEATURES


Triple Sealing Stem with 2 FKM O-Rings and 2nd Generation PTFE Seal Corrosion Resistant Brass
Blow-Out Proof Stem
100% Leak Tested
100% Made in Italy
Leakproof Stem - Lifetime Warranty
29 in-Hg Vacuum Rating
Accessories Available

CERTIFICATIONS/APPROVALS

Conforms to IAPMO PS 117

PRESSURE/TEMPERATURE RATING

250 WOG Max. 250°F



MATERIALS

No.	Part	Material
1	Body	Brass - C35330
2	End Connection	Brass - C35330
3	Ball	T.E.A. Coated Brass - C37700
4	Seat (2)	PTFE G300
5	Stem	Brass - C35330
6	Packing	PTFE G300
7	Stem O-ring (2)	FKM
8	Packing Gland	Brass - C35330
9	Handle	Steel - Geomet® Plated
10	Handle Nut	Steel - Geomet® Plated
11	O-ring (2)	EPDM

DIMENSIONS

Part No	Size	Α	В	С	D	E	C_{v}
100-203	1/2"	3.54	1.53	2.95	0.59	1.24	16.82
100-204	3/4"	3.84	1.95	3.74	0.79	1.28	34.8
100-205	1"	4.31	2.4	4.75	0.97	1.38	52.2
100-206	1-1/4"	4.8	2.59	4.75	1.23	1.3	112.52
100-207	1-1/2"	5.61	3.22	6	1.49	1.5	174
100-208	2"	7.16	3.4	6	1.99	2.01	255.2