


Lead Free Brass Ball Valve

2 Piece, Full Port, Press XLC Connection, 250 WOG

JP-150G XLC



FEATURES

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- 29 in-Hg Vacuum Rating
- Wetted Surfaces Contain Less than .25% Lead Content

CERTIFICATIONS/APPROVALS

- NSF 61-8
- NSF 372
- Conforms to IAPMO PS 117

PRESSURE/TEMPERATURE RATING

- 250 WOG
- Max. 250°F

MATERIALS

No.	Part	Material
1	Body	Lead Free Brass - C46500
2	Seat	PTFE
3	Ball	Stainless Steel
4	Packing	PTFE
5	O-ring	Buna-N
6	Stem	Stainless Steel
7	Handle Nut	Steel - Chrome Plated
8	Handle	Steel - Chrome Plated
9	Packing Nut	Brass - C37700
10	O-Ring	NBR
11	Cap	Lead Free Brass - C46500
12	O-Ring	EPDM

DIMENSIONS

Part No	Size	A	B	C	D
150-209XLCG	2-1/2"	7.48	2.52	4.25	7.76
150-210XLCG	3"	8.17	2.89	4.59	8.19
150-211XLCG	4"	9.86	3.84	5.49	9.25



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.