



Lead Free Bronze Y-Strainer

Solder Connection, 20 Stainless Steel Mesh, 150 WOG

S-651G



FEATURES

Dezincification Resistant Bronze
Residential and Commercial Applications
1/2" - 3/4": 3/8" FNPT Plugged Cap
1" - 3": 1/2" FNPT Plugged Cap
Wetted Surfaces Contain Less than .25% Lead Content

CERTIFICATIONS/APPROVALS

Truesdail Certified


- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372

MSS SP-25

PRESSURE/TEMPERATURE RATING

150 WOG

Max Temperature 250°F



MATERIALS

1 Body Cast Bronze - C89844 2 Filter 304 Stainless Steel - 20 Mesh Screen 3 Packing Fibre
3 Packing Fibre
4 Bonnet Cast Bronze - C89844
5 Plug Cast Bronze - C89844

DIMENSIONS

Part No	Size	Α	В	D	E	F
106-403G	1/2"	3.42	2.83	0.45	0.61	0.57
106-404G	3/4"	4.31	3.27	0.45	0.83	0.59
106-405G	1"	6.1	3.78	0.52	1	0.59
106-406G	1-1/4"	5.9	4.37	0.52	1.29	0.59
106-407G	1-1/2"	6.89	4.82	0.52	1.64	0.59
106-408G	2"	8.62	5.9	0.52	2.03	0.59