



Lead Free Brass Ball Valve

2 Piece, Full Port, Threaded x Hose Connection with Hose Cap, 600 WOG

T-100HCG




FEATURES


Dezincification Resistant Brass Alloy
Triple Sealing Stem with 2 FKM O-Rings and PTFE G300
Hose Connection with Strapped Cap
Blow-out Proof Stem
100% Leak Tested
100% Made in Italy
Leakproof Stem - Lifetime Warranty
Wetted Surfaces Contain Less than .25% Lead Content

CERTIFICATIONS/APPROVALS

NSF/ANSI/CAN 61-G ANSI B1.20.1 ANSI B1.20.7 Meets ISO 6509

VALVE SEAT RATING





MATERIALS

No.	Part	Material
1	Body	Lead Free Brass - C27453
2	Seat (2)	PTFE G300
3	Stem	Lead Free Brass - C28500
4	O-Ring (2)	FKM
5	Ball	T.E.A. Coated Lead Free Brass - C28500
6	Packing	PTFE G300
7	Packing Gland	Brass - C38500
8	End Connection	Lead Free Brass - C27453
9	Handle	Steel
10	Nut	Steel
11	Tether	PVC
12	Cap	Brass - C37700
13	Gasket	NBR

DIMENSIONS

Part No	Size	Α	В	С	D
100-753G	1/2" NPT x 3/4" Hose	2.75	1.57	0.59	4.53
100-754G	3/4" NPT x 3/4" Hose	3.01	2.01	0.79	5.43