



## **Bronze Ball Valve**

2 Piece, Full Port, Threaded Connection, Stainless Steel Trim, Insulated Handle, 600 CWP

## T-200CSS-IH




### **FEATURES**


Dezincification Resistant Bronze Blow-Out Proof Stem Heavy Commercial Pattern 100% Leak Tested 29 in-Hg Vacuum Rating

### **CERTIFICATIONS/APPROVALS**

Threads According to ANSI B1.20.1 Meets MSS SP-110

# VALVE SEAT RATING





#### **MATERIALS**

IMAI ERIALS						
No.	Part	Material				
1	Body	Bronze - C84400				
2	Tailpiece	Bronze - C84400				
3	Ball	Stainless Steel 316				
4	Stem	Stainless Steel 316				
5	Packing Nut	Brass - C36000				
6	Seat (2)	PTFE				
7	Packing Gland	PTFE				
8	Thrust Washer	PTFE				
9	Handle Nut	Steel - Geomet® Plated				
10	Slide	Chrome Plated Steel				
11	Base Plate	Chrome Plated Steel				
12	Foam Insert	Polystyrene				
13	Handle	Nylon				
14	Cap	LDPE				
15*	Sleeve	CAB Tubing				

<sup>\*</sup>Not Pictured

#### **DIMENSIONS**

Part No	Size	Α	В	С	D
200-701-IH	1/4"	1.97	4.25	4.25	0.37
200-702-IH	3/8"	1.97	4.3	4.25	0.37
200-703-IH	1/2"	2.43	4.36	4.25	0.50
200-704-IH	3/4"	2.79	4.65	4.25	0.75
200-705-IH	1"	3.28	4.82	4.25	0.98
200-706-IH	1-1/4"	3.68	4.98	4.25	1.24
200-707-IH	1-1/2"	4.08	5.48	5.51	1.5
200-708-IH	2"	4.59	5.79	5.51	1.97

