

Bronze Ball Valve

3 Piece 4 Bolt, Full Port, Threaded Connection, Stainless Steel Trim, Locking Handle, 600 WOG

T-200SS-4B





FEATURES

Dezincification Resistant Bronze
Locking Device Comes Standard
Blow-Out Proof Stem
Heavy Commercial Pattern
100% Leak Tested
Wetted Surfaces Contain Less than .25% Lead Content

VALVE SEAT RATING

600 CWP





MATERIALS

No.	Part	Material
1	Body	Bronze – C84400
2	Cap	Bronze – C84400
3	Ball	Stainless Steel 316
4	Stem	Stainless Steel 316
5	Seat	PTFE
6	Thrust Washer	PTFE
7	O-Ring	NBR
8	Gland Packing	PTFE
9	Body Seal	PTFE
10	Gland	Brass C3604
11	Cap Nut	Steel ASTM A1008
12	Cap Bolt	Steel ASTM A1035
13	Handle	Steel ASTM A1008
14	Handle Cover	PVC
15	Handle Nut	Steel ASTM A1008

DIMENSIONS

Part No	Size	Α	В	С	D
500-703-LH	1/2"	3.82	1.93	2.90	0.59
500-704-LH	3/4"	3.82	2.01	3.19	0.81
500-705-LH	1"	4.86	2.50	3.75	0.98
500-706-LH	1-1/4"	4.86	2.68	4.13	0.81
500-707-LH	1-1/2"	5.89	3.27	4.35	1.50
500-708-LH	2"	5.89	3.66	5.24	1.97