

# Thread Sealant



## Fast-Drying Hard-Set Thread and Gasket Sealant



WOG Plus

Part #	Size	Case Qty
400-302	4 oz can	24
400-303	8 oz can	24
400-304	16 oz can	12
400-305	32 oz can	12

**Warning: Combustible mixture**  
**Do not use near heat, spark, or open flame.**  
**Do not apply to hot surfaces.**  
**Keep out of reach of children.**

### Recommended for use with:

- Acids, Diluted
- Air, Compressed Gaseous
- Alkalis Diluted
- Ammonia
- Aliphatic Solvents
- Brine
- Butane
- Carbon Dioxide
- Castor Oils
- Chlorinated Water
- Cutting Oils
- Diesel Fuel Oil
- Freon (All)
- Gasoline\*
- Heating Oils
- Helium Gaseous
- Hydraulic Oils
- Inert Gases, Gaseous
- Jet Fuel (JP 3,4,5)
- Kerosene
- Lacquer
- Liquefied Petroleum Gases
- Manufactured Gases
- Mineral Oils
- Naphtha
- Natural Gas
- Nitrogen, Gaseous
- Petroleum Solvents

- Propane
- Refrigeration Gases
- Soap, Liquid
- Steam Lines
- Sugar, Liquid
- Vegetable Oils
- Water (Hot or Cold)
- Xylol

**NOT FOR USE ON OXYGEN**  
**NOT RECOMMENDED FOR USE ON ETHANOL**

\*Contact Jomar for compatible blends

### Recommended for use on:

- All types of metal
- Pipe threads
- Pumps
- Electrical transmission equipment
- Gasoline engines
- Diesel engines
- Tank seams

### Description

Jomar's W.O.G Plus is a fast drying, hard setting, semi-paste, thread and gasket sealer. It remains flexible, so vibrations will not loosen connection. W.O.G plus seals tightly but allows for disassembly without damage to parts. It is lead free, halogen free, non-corrosive and nontoxic.

### Temperature and Pressure Ratings

Brushable to: -50°F (-45°C)  
Flash Point: TTC 58°F (14°C)  
Ignition Temp: 901°F (482°C)  
Temperature Range: -50°F to 400°F (-45°C to 204°C)  
Pressure Ratings: Gas – 2500 PSI (176 kg/cm<sup>2</sup>)  
Liquid – 10,000 PSI (703 kg/cm<sup>2</sup>)  
VOC: 294 g/l

### Approvals

- Meets Mil. Spec. MIL-S-7916B

### Threaded Directions

Stir well before using. Clean threads. Brush liberally onto male threads only. Allow to set for 5 minutes. Make up joint and apply appropriate torque as required. Keep container closed at all times when not in use.

### Flange / Gasket Directions

Stir well before using. Clean flange and gasket. Brush liberally onto both sides of flange and gasket. Allow to set for 5 minutes. Assemble in a normal manner. Keep container closed at all times when not in use.



#### Precautionary Statements

**P264:** Wash skin thoroughly after handling. **P280:** Wear protective gloves and eye protection. **P303 + P361:** IF ON SKIN, immediately remove all contaminated clothing and wash before reuse. **P305 + P351:** IF IN EYES, remove contact lenses if present and easy to do so, rinse with water for several minutes. **P337 + P313:** If eye or skin irritation persists – get medical advice/attention. **P403 + P223:** Store in a cool, well-ventilated place. Keep container tightly closed.